

VELOCICALC[®] Rotating Vane Anemometers

TSI's VELOCICALC Rotating Vane Anemometers accurately measure air velocity and temperature, calculate flow rate, perform averaging, and determine minimum and maximum readings. In addition, the Model 8324 provides data logging capability.

Features and Benefits

All Models

- 4-inch diameter rotating vane head provides reliable (weighted average of) velocity readings
- Sweep mode makes it easy to sweep across an area for one overall measurement
- Flow rate feature calculates volumetric flow (when the user inputs the duct shape and size, or area)
- NIST* traceable calibration certificate

Model 8321

- Displays temperature and velocity simultaneously
- Vane head swivels 270 degrees so display always faces the operator
- Easy, push button operation



Model 8321

Models 8322 and 8324

- Sampling function records multiple point measurements
- Statistics function displays average, maximum and minimum values, and the number of recorded samples
- Variable time constant modes available for a steady display when measuring fluctuating flows
- Optional 36-inch telescopic probe with an articulated swivel head
- Optional portable printer provides hard copy documentation of your readings



Model 8324

Model 8324 Data Logging Features

- Allows user to log 2,849 samples with a time and date stamp
- Single point and continuous modes to fit your application
- Data can be reviewed on-screen, printed and downloaded to a computer spreadsheet program
- TSI downloading software permits easy data transfer to a computer

Applications

- Heating and cooling coil analysis
- Diffuser and grille measurements
- Fume hood face velocity tests
- Indoor air quality tests
- Filter face velocity measurements

Specifications

Models 8321, 8322 and 8324 VELOCiCALC

	Models 8322 and 8324	Model 8321
Velocity		
Range	50 to 6,000 ft/min (0.25 to 30 m/sec)	50 to 6,000 ft/min (0.25 to 30 m/sec); 0.57 to 68 mph (0.9 to 110 km/hr)
Resolution	1.0 ft/min (0.01 m/sec)	1.0 ft/min (0.001 m/sec or 0.01 mph)
Accuracy	±1.0% of reading or ±3 ft/min (±0.015 m/sec), whichever is greater	±1.0% of reading or ±5 ft/min (±0.025 m/sec), whichever is greater
Temperature		
Range	32 to 176°F (0 to 80°C)	32 to 140°F (0 to 60°C)
Resolution	0.1°F (0.1°C)	1°F (1°C)
Accuracy	±1.0°F (±0.5°C)	±2.0°F (±1.0°C)
Volumetric Flow Rate		
Range	0 to 2.6 × 10 ⁶ ft ³ /min** (0 to 1.23 × 10 ⁶ l/sec or 0 to 4.36 × 10 ⁶ m ³ /hr)	4 to 5.4 × 10 ⁶ ft ³ /min† (1.9 to 2.5 × 10 ⁶ l/sec or 6.8 to 9.174 × 10 ⁶ m ³ /hr)
Resolution	0.1 ft ³ /min (0.01 l/sec or 0.01 m ³ /hr)	1.0 ft ³ /min (0.1 l/sec or 0.1 m ³ /hr or 0.001 km.hr)
Averaging	Up to 255 values each of velocity and temperature	N/A
Data Logging (Model 8324 only)		
Range	Up to 2,849 samples and 1,000 test IDs	N/A
Intervals	1, 2, 5, 10, 15, 20, 30, 60 sec; 2, 5, 10, 15, 20, 30, 60 min	N/A
Time Constant	1, 2, 5, 10, 15, 20 sec intervals	N/A
Operating Temperature		
Electronics	40 to 113°F (5 to 45°C)	32 to 140°F (0 to 60°C)
Probe	32 to 176°F (0 to 80°C)	32 to 140°F (0 to 60°C)
Storage Temperature	-4 to 140°F (-20 to 60°C)	14 to 140°F (-10 to 60°C)
Display	4-digit LCD, 0.6 in. (15 mm) digit height	4-digit LCD, 0.45 in. (11 mm) digit height, 2.5-digit LCD, 0.15 in. (3.8 mm) high temperature indicator
Power	4 AA batteries (included) or optional AC adapter	4 AA batteries (included)
Battery Life	Approximately 24 hr continuous use	Approximately 24 hr continuous use
Dimensions (L × H × D)		
Electronics	3.9 × 6.6 × 1.5 in. (10 × 16.8 × 3.8 cm)	11.5 × 4.0 × 1.8 in. (29.2 × 10.2 × 4.7 cm) vane head included
Vane Head	4.0 in. (100 mm) standard head	4.0 in. (100 mm)
Weight (with batteries)	1.5 lb (0.68 kg)	13.1 oz (0.37 kg)
Printer Interface	1200 baud serial interface	N/A

Specifications are subject to change without notice.

Model	Velocity	Temperature	Volumetric Flowrate	Sweep Mode	Averaging Capability	Variable Time Constant	Data Logging/Downloading	Review Data	Printer Output	NIST* Calibration Certificate
8321	•	•	•	•	•	•	•	•	•	•
8322	•	•	•	•	•	•	•	•	•	•
8324	•	•	•	•	•	•	•	•	•	•

*U.S. National Institute of Standards and Technology

**Actual range is a function of maximum velocity and duct size.

†Actual range is a function of velocity × area input where area input is 0.08 to 900 ft² (0.007 to 83 m²).



TSI Incorporated

Corporate Headquarters—Tel: 651 490 2811 Toll Free: 1 800 874 2811 Fax: 651 490 3824 E-mail: answers@tsi.com

TSI China—Tel: +86-10-8260 1595 Fax: +86-10-8260 1597 E-mail: tsibeijing@tsi.com

Contact TSI or visit www.tsi.com for information on specific office locations worldwide.

